

CONCRETE

VINYL TILE

Product Specifications

Type of flooring	EN 649	Heterogeneous PVC
Size	EN 427	45.72cm x 45.72cm
Total Thickness	EN 428	3.0mm
Thickness of wearlayer	EN 429	0.5mm
Edges		square
Performance Classification	EN 685	23, 33,41
Weight/m ²	EN 430	About 5.50kg
Number of pieces/carton		16 tiles = 3.34m ²
Weight per carton		About 18.36kg
Cartons per pallet		52 cartons
Abrasion resistance	EN 660-2	1.1mm ³ /100T
Residual indentation	EN 433	pass
Fire	DIN 4102 EN13501-1	B1
		Cfl-s1
Smoke	Önorm B3810	Q1
Impact sound improvement	ISO 717/2 (DIN 52210)	about 5 dB
Colour fastness	ISO 105-B02 (DIN 53389)	≥ 6
Classification of anti-slip properties	DIN 51130	R 9
Resistance to chemicals	EN 423	Conforms *
Surface treatment		PU
Suitable for floor heating		Yes - refer to installation instructions
Castor chair suitability	EN 425	Yes
Cleaning and Maintenance		Refer to maintenance instructions

* in case of short exposure to normal, domestic chemical agents

Please contact EarthWerks if you need any further information:

Cape Town Tel 021 464 4320
Johannesburg Tel 011 608 4270
www.earthwerks.co.za